

Project:	Operator Plant Training	RA No:	60A	Review Date 31/01/2027
Operation / Task:	Training Grounds Operations	Persons at risk:	Trainers, Trainees, Visitors, Drivers.	
Location / Area:	City & Guilds Training & L Lynch Training, Burntwood, WS7 3GF	Public at risk:	No	
Monitoring Responsibility:	HSQE Team, Recruitment Manager, Training Manager, Trainer			

KEY		S = Severity Rating	L = Likelihood of Occurrence	RR = Risk Rating	
Most effective					

Activity	Hazards/Risks Identified	Risk Rating			Control Measures	Residual Risk			Responsibility
		S	L	RR		S	L	RR	
Arrival at site entrance Vehicle movements across the site Driving vehicles & plant around the training ground Walking across the training ground	Traffic movement or obstruction, incorrect access point used, unfamiliarity with site rules, poor communication, poor plant condition, inadequate certification, struck-by or crush injury, slips and falls, pinch points, collision with people, plant or structures, speeding, wrong direction, unauthorised use.	4	3	12	- All personnel must report to the training facility supervisor before entering site. - All drivers/deliveries must be booked in 48hrs before arrival. - Deliveries to training area will only be agreed by L Lynch/City & Guilds Staff to ensure they are gained access - All visitors must sign in and attend a full site induction. - Site rules, traffic routes and speed limits must be briefed, understood and followed; route plans must be displayed. - Traffic signage must be displayed. - Mandatory PPE must be worn in accordance with the SSOW. - Delivery or collection documentation must be reviewed prior to any movement permitted. - Plant condition must be checked for leaks, damage and safety-critical defects; service logs and driver/operator competencies must be verified (A50/68). - The training ground must be segregated using fencing/barriers. - Good site housekeeping standards to be maintained. - Pedestrian routes available, segregated and clearly marked. - Pedestrians must remain within designated walkways and crossing points. - Reversing alarms and beacons must be maintained in good working order and used at all times while on site. - Trainer visibility must be maintained at all times. - Access routes must be kept clear at all times.	4	2	8	Recruitment Manager Training Manager Trainer

Owner: Head of HSQE	Version: 3	LF263
Uncontrolled if printed or copied. Always check for latest version.	Internal Use	Page 1 of 5

Project:	Operator Plant Training	RA No:	60A	Review Date 31/01/2027
Operation / Task:	Training Grounds Operations	Persons at risk:	Trainers, Trainees, Visitors, Drivers.	
Location / Area:	City & Guilds Training & L Lynch Training, Burntwood, WS7 3GF	Public at risk:	No	
Monitoring Responsibility:	HSQE Team, Recruitment Manager, Training Manager, Trainer			

KEY	S = Severity Rating	L = Likelihood of Occurrence	RR = Risk Rating
Most effective			

Activity	Hazards/Risks Identified	Risk Rating			Control Measures	Residual Risk			Responsibility
		S	L	RR		S	L	RR	
Loading, unloading plant and ancillary equipment Accessing and exiting plant / vehicle Parking the plant & vehicles in a safe manner	Crush injury, struck-by injury, slips, trips and falls, pinch points, PPI, traffic impact, incorrect tipping location, contamination, entrapment.	4	3	12	- Loading, unloading must only take place in designated areas and in accordance with RA21 Loading Unloading of Plant Transporters by competent drivers (A50/68). - No loading or unloading must take place on the public highway unless separately planned and controlled. - Chains, slings and strops must be certified, in date and attached from ground level. - Tie-downs must be removed from ground level and stored safely. - Three points of contact must be maintained when accessing or exiting vehicles or plant; factory-fitted steps and handrails must be used. - Pedestrian access to the loading/unloading area must be controlled; pedestrians must remain in clear view of the driver/operator. - Exclusion zones and Plant Red Zones must be maintained; no unauthorised personnel permitted unless plant is fully stopped, isolated, and a clear Thumbs-Up signal is given. - Hands must be kept clear of pinch points. - Parking must only take place in designated areas. - Keys must be removed and returned to the office.	4	2	8	HSQE Team Recruitment Manager Training Manager Trainer
Welfare provision	Lack of welfare, dehydration, poor hygiene, inadequate rest facilities	2	2	4	- Welfare facilities including toilets, drinking water, rest areas and classrooms must be provided within close proximity to the training ground. - Welfare access must be included in the site induction. - Welfare facilities must be maintained in a clean, hygienic and serviceable condition. - Suitable shelter must be available for breaks during adverse weather. - Hand-washing facilities must be available and stocked.	2	1	2	HSQE Team / Recruitment Manager / Training Manager / Trainer

Owner: Head of HSQE	Version: 3	LF263
Uncontrolled if printed or copied. Always check for latest version.	Internal Use	Page 2 of 5

Project:	Operator Plant Training	RA No:	60A	Review Date 31/01/2027
Operation / Task:	Training Grounds Operations	Persons at risk:	Trainers, Trainees, Visitors, Drivers.	
Location / Area:	City & Guilds Training & L Lynch Training, Burntwood, WS7 3GF	Public at risk:	No	
Monitoring Responsibility:	HSQE Team, Recruitment Manager, Training Manager, Trainer			

KEY	S = Severity Rating	L = Likelihood of Occurrence	RR = Risk Rating
Most effective </			

Activity	Hazards/Risks Identified	Risk Rating			Control Measures	Residual Risk			Responsibility
		S	L	RR		S	L	RR	
Operating plant on Training Ground	Unclear instructions, environmental impact, plant collision, blind spots, overturning.	3	3	9	- CPCS/NPORS training & testing standards and lesson plans to be followed at all times - Plant must be shut down and secured when unattended. Misuse of plant will result in removal from the training ground. - Only one plant item must operate within each designated zone. - Exclusion zones must be maintained. - Trainer visibility must be maintained at all times. - Plant to be operated on firm, level ground. - The training ground must be used in accordance with its intended design. - Plant training must be carried out in line with lesson plans.	3	2	6	HSQE Team Recruitment Manager Training Manager Trainer
Wellbeing	Fatigue, site security, unauthorised access, violence.	3	3	9	- Regular breaks must be scheduled throughout the training day. - Training activities must be paused if weather conditions create unsafe ground conditions or visibility issues. - Noise and vibration exposure must be managed in line with CPCS training durations and lesson plans. - Access to the training ground must be controlled at all times; only authorised personnel may enter the facility. - Visitors must sign in and be accompanied at all times while on site. - Perimeter fencing, gates and access points must be secured to prevent unauthorised entry. - Trainers to be in possession of a "kill switch" during training. - Report any suspicious behaviour to training manager & City & Guilds immediately. Report any suspicious behaviour to training manager & City & Guilds immediately.	3	2	6	

Owner: Head of HSQE	Version: 3	LF263
Uncontrolled if printed or copied. Always check for latest version.	Internal Use	Page 3 of 5

Project:	Operator Plant Training	RA No:	60A	Review Date 31/01/2027
Operation / Task:	Training Grounds Operations	Persons at risk:	Trainers, Trainees, Visitors, Drivers.	
Location / Area:	City & Guilds Training & L Lynch Training, Burntwood, WS7 3GF	Public at risk:	No	
Monitoring Responsibility:	HSQE Team, Recruitment Manager, Training Manager, Trainer			

KEY	S = Severity Rating	L = Likelihood of Occurrence	RR = Risk Rating
Most effective			

Activity	Hazards/Risks Identified	Risk Rating			Control Measures	Residual Risk			Responsibility
		S	L	RR		S	L	RR	
					- A zero-tolerance approach to violence, aggression or threatening behaviour must be enforced; any incident must be escalated in accordance with company procedures. - Staff must not work alone in isolated areas of the training ground without communication equipment and supervisor awareness. - Emergency contact procedures must be briefed during induction and accessible to all personnel.				
Environmental Conditions	Ground contamination, airborne dust, noise exposure, fuel spills, poor air quality, environmental nuisance.	3	3	9	- Training ground surfaces must be maintained to minimise airborne dust; water suppression must be used during dry conditions where required. - Noise exposure must be managed in accordance with training durations and PPE requirements; hearing protection must be worn where identified in the SSOW. - Spill kits must be provided at refuelling and plant parking areas; spills must be contained and managed in accordance with RA47 Spill Response. - Refuelling must be carried out only in designated areas with drip trays or hard-standing surfaces. - HVO or low-emission fuels must be used where available to reduce environmental impact. - Engines must not be left idling unnecessarily; plant must be shut down when not in use. - Waste materials must be segregated and disposed of in accordance with site waste procedures. - Activities must be paused if weather conditions create unsafe or environmentally harmful conditions (e.g., high winds causing dust migration).	3	2	6	HSQE Team / Recruitment Manager / Training Manager / Trainer
Emergency Response - accidents, first	Delayed response, incorrect treatment, escalation of	4	3	12	- Situations must be assessed without placing personnel in danger. - The scene must be made safe where possible. - First aid must only be provided by trained personnel following DRABC.	4	2	8	HSQE Team Recruitment Manager

Owner: Head of HSQE

Version: 3

LF263

Uncontrolled if printed or copied. Always check for latest version.

Internal Use

Page 4 of 5

Project:	Operator Plant Training	RA No:	60A	Review Date 31/01/2027
Operation / Task:	Training Grounds Operations	Persons at risk:	Trainers, Trainees, Visitors, Drivers.	
Location / Area:	City & Guilds Training & L Lynch Training, Burntwood, WS7 3GF	Public at risk:	No	
Monitoring Responsibility:	HSQE Team, Recruitment Manager, Training Manager, Trainer			

KEY	S = Severity Rating	L = Likelihood of Occurrence	RR = Risk Rating
Most effective			

Activity	Hazards/Risks Identified	Risk Rating			Control Measures	Residual Risk			Responsibility
		S	L	RR		S	L	RR	
aid, fire, spill, escalation and reporting	incident, uncontrolled spill, fire growth. Inadequate incident reporting - near misses, unsafe behaviours				- Emergency services must be contacted via 999 or 112 with clear information. - Fire alarms must be raised and evacuation to the muster point carried out. - Only trained fire marshals must attempt to extinguish small fires. - Spill kits must be used to contain contamination; RA47 Spill Response must be followed. - Spill kit locations must be briefed during induction. - Head Office must be notified once the situation is controlled. - Incident details must be recorded factually, including dates, times, names and witness information; accident book must be completed. - The Lynch CIR reporting system must be used for near misses and unsafe acts.				Training Manager Trainer
Paperwork and procedures	Incorrect or missing records, incomplete work, misunderstanding of training programme.	3	3	9	- A site walk must be completed before training commences. - Daily plant checks must be completed and verified before work starts. - Documentation must be checked, signed and completed before departure. - Lesson plans must be followed in full.	3	1	3	Training Manager Trainer

Risk Assessment Prepared By:

Daniela Rizvan

Signature:

29/06/2026

Risk Assessment Reviewed By:

Paul Lynch

Signature:

29/06/2026



Owner: Head of HSQE	Version: 3	LF263
Uncontrolled if printed or copied. Always check for latest version.	Internal Use	Page 5 of 5