










## COSHH ASSESSMENT FORM

Risk Assessment Reference Number: COSHH75		Date of Assessment: 31/10/2025	
Assessor/s: Jamie-Lee Macavoy		Name of Substance: EVO STIK Impact Spray Adhesive	
Date of Safety Data Sheet (SDS): 24/08/2023		Manufacturer: Bostik Ltd	
Use (details of the way it is used): use as per manufacturer guidelines. High strength multi-purpose adhesive.			
Frequency of Exposure: infrequent		Duration of Exposure: short duration	
Workplace Exposure Limit (WEL):	<input type="checkbox"/> Not Assigned	Petroleum gases, liquified Acetone	TWA 1750mg/m3 – STEL 2180mg/m3 TWA 1210mg/m3 – STEL 3620mg/m3
Hazard Warning Symbols associated with substance (circle):			
			
			
			
Explosive	Corrosive	Flammable	Serious Health Hazard
		Health Hazard	Oxidising
		Toxic	Hazardous to Environment
			Gas under Pressure

Worst Case Outcome				
5	4	3	2	1
Fatality	Severe Injury	Lost time Injury	Minor Injury	No Injury

Likelihood				
5	4	3	2	1
Certain	Very likely	likely	Unlikely	Remote

Risk Rating Outcome X Likelihood		
High	Medium	Low
15-25	10-12	1-9

Persons affected by the Activity	Identified Hazards	Control Measures Already in Place	Outcome	Likelihood	Risk Rating	Is further action required Yes/No

Employees/ Contractors/ Others	Respiratory problems due to inhalation	Only trained, competent personnel are authorised to use product. Product only to be used in well-ventilated areas. FFP3 mask available.	2 Minor Injury	2 Unlikely	4 Low	No
Employees	Ingestion (gastrointestinal irritation)	Ensure hands are washed prior to eating, drinking and smoking.	2 Minor Injury	1 Remote	3 Low	No
Employees/ Contractors/ Others	Irritation of eyes and skin/dermatitis due to contact	Eye protection and protective gloves available. EN166 eye protection, EN374 Gloves. Butyl rubber or nitrile rubber >0.7mm thickness. Use barrier creams available. Eye wash station available and adequate supply. Ensure good hygiene practices are followed.	3 Lost time Injury	2 Unlikely	6 Low	No
Employees/ Contractors/ Others	Fire and explosion	Minimal quantities are stored. Ordered as required. Suitable and sufficient fire extinguishers located in works areas. Use dry chemical, CO2 or water spray to extinguish. DO NOT extinguish a leaking gas fire unless leak can be stopped. DO NOT use full water jet.	5 Fatality	1 Remote	5 Low	No
Environment	Pollution and contamination to ground and watercourse	Must be used in line with manufacturer's instructions. Must be disposed of in line with local waste conditions. Stop at source, contain and clean up spill. Avoid release into the environment.	1 No Injury	2 Unlikely	2 Low	No



**COSHH ASSESSMENT FORM Cont.**

Persons affected by the Activity	Identified Hazards	Control Measures Already in Place	Outcome	Likelihood	Risk Rating	Is further action required Yes/No

Further Control Measures						Further Control Measures Follow up		
						Allocated to (Name)	Target date	Date completed
Review date/s:								
Reviewed By:								