



[www.herbstmachinery.com](http://www.herbstmachinery.com)

## Standard 14 Tonne Dump Trailer



### Standard Features

- Sprung Drawbar
- Heavy Duty EN16 Towing Eye
- Mudguards and Flaps
- Hydraulic Brakes

### Optional Features

- Rotary Towing Eye
- Braking System – Air / Oil Options
- Fail Safe Valve / Choke Valve
- 10mm Floor
- Double Acting Rear Door
- Wheels – 550/45 22.5
- Custom Colour



MODEL	14 TONNE HISIDE	14 TONNE HI SPEED
Permissible Total Weight	17,500kg	17,500kg
Unladen Weight	3,500kg	3,750kg
Cubic Capacity	7.00	7.25
Loading Capacity	14,000kg	14,000kg
Maximum Hitch Load	3,500kg	3,500kg
Overall length/Width/Height (mm)	5080 / 2440 / 2380	5400 / 2500 / 2380
Loading Height (mm)	2070	2140
Height of inside of Bin (mm)	1170	1170
Body Length (mm)	3797	3949
Bin Width Top / Bottom (mm)	2250 / 1500	2250 / 1500
Bin Thickness Side / Floor	6mm / 6mm	6mm / 10mm
Chassis	8"	10"
Running Gear	Rocker Beams - 10 Stud Hubs (90 x 90 Beam)	10 Stud Hi Speed axles 9 Leaf springs
Tyres	385/65 22.5	385/65 22.5
Wheel Track Width (mm)	2020	1980
Maximum Speed	50KPH	80KPH
Brake Size	400 X 80	406 X 120
Telescopic Cylinders	2	2
Telescopic Cylinders (No. Of sections / Stroke / Oil)	3 / 200 Bar / 13.0 Litres	3 / 200 Bar / 13.0 Litres
Tipping Angle	71°	71°
Up & over Rear door	2 x Single Acting Cylinders	2 x Double Acting Cylinders

## Contact

### Herbst Machinery Ltd

120 Drumnakilly Road,  
Omagh,  
Co. Tyrone,  
N. Ireland BT79 0JT

Tel: +44 (0)28 8077 1568

Fax: +44 (0)28 8077 1569

General: [info@herbst.co.uk](mailto:info@herbst.co.uk)

Sales: [ashley@herbst.co.uk](mailto:ashley@herbst.co.uk)

Spare Parts: [stores@herbst.co.uk](mailto:stores@herbst.co.uk)