

WA380-8

Specification

Engine	EU Stage V, Komatsu SAA6D107E-6 turbocharged common rail direct injection diesel engine, 143Kw/192hp
Hydraulics	Electronic closed-centre load sensing system
Bucket	3.75m ³ Direct mount with bolt on cutting edge, 2990mm wide
Transmission	Automatic powershift
Tyres	23.5R25 L3's
Lynch Additional Specification	White noise travel alarm Green seat belt warning light Amber beacon Red seat belt Signwriting Komtrax Telematics Hi Viz handrails and steps Additional counterweight Auto lube

Dimension Figures

OPERATING WEIGHT (APPR.)

Operation weight
18,685 kg

Static tipping weight(Straight)
15,485 kg

Static tipping weight(Articulated)
14,946 kg

MACHINE DIMENSIONS

WA380-8

a	Reach at 45°	1360 mm
b	Dump height at 45°	2645 mm
c	Hinge pin height	4095 mm
d	Height top edge of bucket	6010 mm
e	Digging depth	120 mm
f	Max loading height at 45°	2645 mm
A`	Overall length, bucket on ground	8680 mm
B	Wheel base	3300 mm
C	Bucket width	2990 mm
D	Width over tyres	2765 mm
E	Track width	2160 mm
F	Ground clearance	455 mm
H	Overall height	3395 mm

