

WA470-8

Specification

Engine	EU Stage V, Komatsu SAA6D125E-7 turbocharged common rail direct injection diesel engine, 204Kw/273hp
Hydraulics	Electronic closed-centre load sensing system
Bucket	4.5m ³ Direct mount with bolt on cutting edge, 3000 mm wide
Transmission	Automatic powershift
Tyres	26.5R25 L5's
Lynch Additional Specification	White noise travel alarm Green seat belt warning light Amber beacon Red seat belt Signwriting Komtrax Telematics Hi Viz handrails and steps Additional counterweight Auto lube

Dimension Figures

OPERATING WEIGHT (APPR.)

Operation weight
24,565 kg

Static tipping weight(Straight)
20,015 kg

Static tipping weight(Articulated)
17,165 kg

MACHINE DIMENSIONS

WA470-8

a	Reach at 45°	1520 mm
b	Dump height at 45°	2830 mm
c	Hinge pin height	4335 mm
d	Height top edge of bucket	5945 mm
e	Digging depth	125 mm
f	Max loading height at 45°	4020 mm
A`	Overall length, bucket on ground	9575 mm
B	Wheel base	3450 mm
C	Bucket width	3000 mm
D	Width over tyres	2915 mm
E	Track width	2240 mm
F	Ground clearance	505 mm
H	Overall height	3475 mm

